

**CORRIGENDUM – I**

**Date: 15-01-2025**

**NIT NO.CSEZ-CSZA01(2)/14/2022-SEZCochin dated 27-12-2024**

**Tender Reference : CSEZ-CSZA01(2)/14/2022-SEZ**

**Tender ID: 2024\_CSEZA\_783216\_1**

**Name of the work: Extension and Modification of Main canteen at CSEZ unit, Kakkanad.**

**The Tender is amended as follows.**

<b>Sl. No.</b>	<b>Section/Clause in Tender</b>	<b>As per uploaded tender document</b>	<b>Amendment</b>
1	Section I Sl. No.4	Rs. 25,34,875/- (Rupees Twenty-Five Lakhs Thirty Four Thousand Eight Hundred and Seventy Five only/-) excluding GST	Rs. 21,01,635/- (Rupees Twenty-One Lakh One Thousand Six Hundred and Thirty Five only) excluding GST
2	Section I Sl. No.5	Rs. 50,700/- (Refundable) Rupees Fifty Thousand Seven Hundred Only	Rs. 42,033/- [Rupees Forty Two Thousand Thirty Three Only] (Refundable)
3	Section I Sl. No.9	Last date & time for submission of Technical & Financial Bid along with EMD.: 17-1-2025; Time: 15:00 hours	Last date & time for submission of Technical & Financial Bid along with EMD.: 27-1-2025; Time: 15:00 hours
4	Section I Sl. No.10	Opening of Technical Bid: 17-1-2025; Time: 15:30 hours	Opening of Technical Bid: 27-1-2025; Time: 15:30 hours
5	Volume – II Financial Bid C. BILL OF QUANTITIES (BOQ)		BoQ with corrected Serial Numbers is as follows

Sl No	DESCRIPTION	UNIT	QTY	RATE	AMOUNT
<b>Renovation for existing Canteen</b>					
1	Dismantling roofing including ridges, hips, valleys and gutters etc., and stacking the material within 50 metres lead of GS SHEET	M2	85.5		
2	Steel work in built up tubular (round, square or rectangular hollow tubes etc.) trusses etc., including cutting, hoisting, fixing position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. complete.	Kg	468.672		
3	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:	M2	42.75		
4	Providing and fixing precoated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+0.05%), total coated thickness with zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length upto 12 metre or as desired by Engineer-in-charge. The sheet shall be fixed using self drilling/self tapping screws of size (5.5x55mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	M2	85.5		
5	Dismantling aluminium / Gypsum partitions, doors, windows, fixed glazing and false ceiling including disposal of unserviceable surplus material and stacking of serviceable material with in 50 metres lead as directed by Engineer - in-Charge	M2	283.29		
6	Providing and fixing flat pressed 3 layer medium density particle board or graded particle board (Grade I) IS: 3087 marked, in ceiling with necessary nails etc. complete 12 mm thick	M2	283.29		
7	Wall painting with acrylic emulsion paint, having VOC (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture including applying additional coats wherever required, to achieve even shade and colour. One coat	M2	609.6		
<b>Main Canteen Front Extension</b>					
8	Earth work in excavation by mechanical means (Hydraulic excavator)/manual means over areas (exceeding 30 cm in depth, 1.5 m in width as well	M3	19.602		

SI No	DESCRIPTION	UNIT	QTY	RATE	AMOUNT
	as 10 sqm on plan) including disposal of excavated earth, lead up to 50 m and lift up to 1.5 m, disposed earth to be levelled and neatly dressed. All kinds of soil				
9	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level: 1:4:8 (1 cement: 4 coarse sand: 8 graded stone aggregate 40 nominal size)	M3	10.2895		
10	Random rubble masonry with hard stone in foundation and plinth including levelling up with cement concrete 1:6:12 (1 cement: 6 coarse sand: 12 graded stone aggregate 20 mm nominal size) up to plinth level with: Cement mortar 1:6 (1 cement: 6 coarse sand)	M3	17.82		
11	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundation etc. in layers not exceeding 20 cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift up to 1.5 m.	M3	72.18		
12	Centering and shuttering including strutting, etc. and removal of form for: Lintels, beams, plinth beams, girders bressummers and cantilevers	M2	50.42		
13	Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level: 1:2:4 ( 1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size)	M3	8.958		
14	Steel reinforcement for R.C.C work including straightening, cutting, bending, placing in position and binding all complete up to plinth level Mild steel and Medium Tensile steel bars	Kg	895.8		
15	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in: Cement mortar 1:6 (1 cement : 6 coarse sand)	M3	2.8215		
16	12 mm cement plaster of mix: 1:4 ( 1 cement : 4 fine sand)	M2	146.2		
17	Steel work in built up tubular (round, square or rectangular hollow tubes etc.) trusses etc., including cutting, hoisting, fixing position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. complete.	Kg	891.172		

SI No	DESCRIPTION	UNIT	QTY	RATE	AMOUNT
18	Providing and fixing precoated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+0.05%), total coated thickness with zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length upto 12 metre or as desired by Engineer-in-charge. The sheet shall be fixed using self drilling/self tapping screws of size (5.5x55mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	M2	154.0235		
19	Providing and fixing flat pressed 3 layer medium density particle board or graded particle board (Grade I) IS: 3087 marked, in ceiling with necessary nails etc. complete	M2	107.189		
20	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS : 15622, of approved make, in all colours and shades, laid on 20 mm thick cement mortar 1:4(1 cement : 4 coarse sand), including grouting the joints with white cement and matching pigments etc., complete. Size of Tile 600 x 600 mm.	M2	87.97		
21	Wall painting with acrylic emulsion paint, having VOC (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture including applying additional coats wherever required, to achieve even shade and colour. Two coats	M2	719.46		
22	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:	M2	207.82		
<b>ELECTRICAL REWIRING</b>					
23	Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed steel conduit, with piano type switch, phenolic laminated sheet, suitable size MS box and earthing the point with 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable etc as required.	Point	12		
24	Wiring for circuit/ submain wiring along with earth wire with the following sizes of FRLS PVC	Meter	300		

SI No	DESCRIPTION	UNIT	QTY	RATE	AMOUNT
	insulated copper conductor, single core cable in surface / recessed medium class PVC conduit as required-2x1.5 sq.mm + 1x1.5 sq.mm earth wire				
25	Supplying and fixing following modular switch/ socket on the existing modular plate & switch box including connections but excluding modular plate etc. as required.3 pin 5/6 amp socket outlet	each	4		
26	Supplying and fixing following size/ modules, GI box along with modular base & cover plate for modular switches in recess etc as required.6 Module (200mmX75mm)	Each	2		
27	Supplying and fixing following size/ modules, GI box along with modular base & cover plate for modular switches in recess etc as required.12 Module (200mmx 150mm)	each	1		
28	Supplying and fixing of following sizes of medium class PVC conduit along with accessories in surface/ recess including cutting the wall and making good the same in case of recessed conduit as required.20 mm	meter	30		
29	1200 mm sweep- 5 star rated Ceiling fan, complete with 300mm down rod, canopies, shackles and blades and resistance type regulator working on 230/240V single phase A/C	EACH	4		
30	Supply and fixing 12watt LED light	EACH	8		
<b>PLUMBING WORKS</b>					
31	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold-water supply, including all CPVC plain & brass threaded fittings including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer -in-Charge. - Exposed on wall-20 mm nominal outer dia pipes	Meter	30		
32	Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require: White Vitreous China Wash basin size 630x450 mm with a pair of 15 mm C.P. brass pillar taps	EACH	3		
33	Providing and fixing P.V.C. waste pipe for sink or wash basin including PVC. waste fittings complete. Semi rigid pipe.40 mm dia	M	6		
	<b>TOTAL Cost</b>				

**Sd/-  
Secretary-in-charge**